



COPY OF PAPERS  
ORIGINALLY FILED

PATENT  
450117-03752

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants : Daniela RADDINO et al.  
Serial No. : 10/021,776  
Filed : December 12, 2001  
For : METHOD FOR RECOGNIZING SPEECH  
Art Unit : 2641

745 Fifth Avenue  
New York, New York 10151  
Tel. (212) 588-0800

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to:  
Assistant Commissioner for Patents  
Washington, D.C. 20231, on April 12, 2002

Glenn F. Savit, Reg. No. 37,437

Name of Applicant, Assignee or  
Registered Representative

Signature

April 12, 2002

Date of Signature

CLAIM OF PRIORITY

Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

In support of the claim of priority under 35. U.S.C.  
§ 119 asserted in the Declaration accompanying the above-entitled application, as filed, please find enclosed herewith a certified copy of European Application No. 00 127 377.0, filed in Europe on 13 December 2000 forming the basis for such claim.

**THIS PAGE BLANK (USPTO)**

PATENT  
450117-03752

Acknowledgment of the claim of priority and of the  
receipt of said certified copy(s) is requested.

Respectfully submitted,

FROMMER LAWRENCE & HAUG LLP  
Attorneys for Applicants

By: 

Glenn F. Savit  
Reg. No. 37,437  
Tel. (212) 588-0800

Enclosure(s)

**THIS PAGE BLANK (USPTO)**



Europäisches  
Patentamt



European  
Patent Office

Office européen  
des brevets

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

00127377.0

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

R C van Dijk

DEN HAAG, DEN  
THE HAGUE, 10/12/01  
LA HAYE, LE

**THIS PAGE BLANK (USPTO)**



**Europäisches  
Patentamt**

**European  
Patent Office**

**Office européen  
des brevets**

**Blatt 2 der Bescheinigung  
Sheet 2 of the certificate  
Page 2 de l'attestation**

Anmeldung Nr.:  
Application no.:  
Demande n°: 00127377.0

Anmeldetag:  
Date of filing: 13/12/00  
Date de dépôt:

Anmelder:  
Applicant(s):  
Demandeur(s):  
**Sony International (Europe) GmbH**  
10785 Berlin  
GERMANY

Bezeichnung der Erfindung:  
Title of the invention:  
Titre de l'invention:  
**Method for recognizing speech**

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:  
State:  
Pays:

Tag:  
Date:  
Date:

Aktenzeichen:  
File no.  
Numéro de dépôt:

Internationale Patentklassifikation:  
International Patent classification:  
Classification internationale des brevets:  
**G10L15/14**

Am Anmeldetag benannte Vertragsstaaten:  
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE/TR  
Etats contractants désignés lors du dépôt:

Bemerkungen:  
Remarks:  
Remarques:

THE UNITED STATES OF AMERICA  
DEPARTMENT OF COMMERCE  
BUREAU OF PATENT AND TRADEMARKS

OFFICE OF THE COMMISSIONER OF PATENTS AND TRADEMARKS  
WASHINGTON, D. C. 20530

TO: THE COMMISSIONER OF PATENTS AND TRADEMARKS  
FROM: [Name]  
SUBJECT: [Subject]

DATE: [Date]

RE: [Subject]

**THIS PAGE BLANK (USPTO)**



**MÜLLER & HOFFMANN PATENTANWÄLTE**

European Patent Attorneys - European Trademark Attorneys

Innere Wiener Strasse 17  
D - 81667 München

**EPO - Munich**  
48

**13. Dez. 2000**

Attorney's File: 52886 Gö/Ko/as

13.12.2000

Client's Ref.: S00P5197EP00

PAE00-084HNCE

**SONY INTERNATIONAL (EUROPE) GmbH**

Kemperplatz 1  
10785 Berlin  
GERMANY

---

**METHOD FOR RECOGNIZING SPEECH**

---

## MÜLLER &amp; HOFFMANN

- 2 -

Sony International (Europe) GmbH

File: 52.886

13.12.2000

EPO - Munich  
48

13. Dez. 2000

**Description**

1 The present invention relates to a method for recognizing speech according to the preamble of claim 1 and in particular to a method for recognizing speech using a process of penalty-based keyword spotting.

5 Methods for recognizing speech are often confronted with speech phrases or word sequences which are not part of a given vocabulary within a predefined language model or grammar. These out-of-vocabulary words are called garbage speech in contrast to in-vocabulary words which are called keywords for example.

10

In known methods for recognizing speech at least the keywords in a received speech phrase are recognized in particular by employing a keyword spotting based recognition process and a given language model. To consider the keywords as well as the out-of-vocabulary words or the garbage a combination of at least one first language or keyword model and one second language, one out-of-vocabulary model or garbage model is used in said language model underlying the recognition process. The keyword models contain and/or describe possible in-vocabulary or keywords or phrases. The out-of-vocabulary or garbage models describe at least a part of the out of vocabulary words or phrases.

20

In conventional methods for recognizing speech employing a language model as described above the problems occurs that the out-of-vocabulary or garbage model and the associated grammar more often fit better than the keyword model. Therefore, in conventional methods for recognizing speech one has an increased amount of false rejected keywords as an increased number of phrases are classified as being out of the vocabulary of the keyword model.

It has therefore been suggested to introduce a penalty into the garbage model or out-of-vocabulary model to encourage and increase the recognition and output of keywords. The penalty is introduced into the calculation of the global score or likelihood of a given phrase or utterance of being contained in the out-of-vocabulary or garbage model. The so modified or penalized global score or likelihood for the garbage model is compared with the respective global scores or likelihoods for the keywords or keyword model. As the penalty decreases the global score or likelihood for the garbage model, the recognition and output for keywords is increased.

MÜLLER &amp; HOFFMANN

- 3 -

Sony International (Europe) GmbH

File: 52.886

13.12.2000

1 In many applications the so described word spotting procedure is too rigid as it does not consider e.g. the application situation as well as user preferences or certain details of the speech input or the recognition process per se.

5 It is an object of the present invention to provide a method for recognizing speech which is particular accurate and flexible.

The object is achieved by a method for recognizing speech as mentioned above according to the present invention with the characterizing features of claim 1.

10 Preferred and advantageous embodiments of the inventive method for recognizing speech are subject of the dependent subclaims.

The inventive method for recognizing speech is characterized in that at least one variable penalty value is associated with and/or used to define the global penalty. It is therefore a basic idea of the present invention to make variable the penalty introduced into the language model and in particular to the garbage model so as to increase the keyword output. Consequently the global penalty can be adjusted to consider e.g. the recognition situation, user preferences as well as internal properties of the recognition process per se. As a result, the inventive method for recognizing speech is more flexible and more accurate with respect to prior art methods.

The global penalty can be made variable by introducing a single variable penalty value or a set of fixed and/or variable penalty values. Using a set of fixed penalty values makes the global penalty variable for instance by creating different combinations of said fixed penalty values in dependence of the recognition process per se, user preferences and/or the like.

To increase the variability of the inventive method for recognizing speech said variable penalty value is in each case dependent on or a function of the recognition process, of an user input, of a received speech phrase and/or their characteristics or the like. As a result, the variable penalty values may consider in a real-time manner actual needs of the recognition process and the application situation. By these measures the flexibility and the accuracy of the method is further increased.

## MÜLLER &amp; HOFFMANN

- 4 -

Sony International (Europe) GmbH

File: 52.886

13.12.2000

- 1 In a further preferred and advantageous embodiment of the inventive method for recognizing speech at least one statistical model, a garbage model or the like is used as said out-of-vocabulary model.
- 5 It is also preferred that said out-of-vocabulary model and in particular said garbage model is chosen to contain at least a phone\* grammar or the like. Using a phone\* grammar ensures that any utterance being composed as a sequence of phones, phonemes, syllables or the like will fit besides the keyword model at least in the garbage model. This further ensures that for any utterance the
- 10 method determines whether said utterance is recognized by being contained in the keyword model or whether it is rejected as being contained in the garbage model; there is no third possibility.

A particular simple embodiment of the inventive method for recognizing speech

15 can be achieved by associating said variable penalty value with a transition of a recognition process to and within an out-of-vocabulary model, in particular from a keyword model. This is a very simple measure to increase the recognition and the output of keywords with respect to garbage words.

- 20 In an preferred embodiment said variable penalty is - in particular in each case - associated with a recognition step of said recognition process carried out within said out-of-vocabulary model or a garbage model and/or a recognition or processing time of said recognition process spent within said out-of-vocabulary model or garbage model. That means, that depending on the time or the number
- 25 of steps the recognition process remains within the garbage model the likelihood of a recognition result within the garbage model is stronger penalized. This ensures that only for case for which any recognition result from the keyword model is beaten by a certain result in the garbage model a rejection takes place. If on the other hand a certain possibility is given for a keyword and an in-vocabulary word a keyword is output.
- 30

In a particular embodiment of the inventive method for recognizing speech a lattice structure of recognition paths or the like is used in said keyword model and/or said out-of-vocabulary or garbage model. According to this embodiment

35 each path within the lattice is associated with a possible keyword or a garbage word, respectively. Every time the method enters a certain path to the garbage model a distinct penalty will be associated and will decrease the likelihood of the path to and within the garbage model and therefore of the certain garbage

1 word. It is preferred to associate with at least a part of said recognition path in  
said lattice structure in said out-of-vocabulary model a variable penalty value in  
particular within the statistical information of said out-of-vocabulary model or  
garbage model.

5

In a further preferred embodiment of the inventive method for recognizing  
speech a Markov model, in particular a single state Markov model, is at least  
contained in said out-of-vocabulary or said garbage model. In that particular  
case a variable penalty value is associated with self-transitions of said recogni-  
10 tion process within said Markov model.

To further increase the flexibility of the inventive method the variable penalty  
value is made dependent on the particular application, the application status  
and/or on the user preferences or the like. It is further preferred that said vari-  
15 able penalty value is varied interactively, in particular by a user action via a  
user interface.

Alternatively or additionally the flexibility and adjustability of the inventive  
method can be increased when said variable penalty value is hold and/or stored  
20 in an randomly accessible manner in particular within the model statistical in-  
formation of the language model.

The inventive method can advantageously be realized by determining likeli-  
hoods, global scores or the like for a recognition result in said keyword model  
25 and in said out-of-vocabulary model - in particular said garbage model - the lat-  
ter of which being variable penalized and by accepting recognition result for the  
case that a keyword model likelihood is larger than a out-of-vocabulary model  
likelihood. Otherwise the recognition result is rejected.

30 Some main aspects and properties of the method for recognizing speech accord-  
ing to the invention can be summarized as follows:

Conventional methods for recognizing speech employing word spotting systems  
aim to spot keywords inside a free vocabulary sentence. The keywords may be  
35 the words of the application vocabulary. All other words are called out of vo-  
cabulary words or garbage. A statistical model, called garbage model or the like,  
is trained to match all these out-of-vocabulary words.

- 1 The keyword models and garbage models are in competition in a word spotting system. The two likelihoods of the two, keyword model and of the garbage model, respectively, are compared and the one with the lower likelihood is rejected.
- 5 To increase and encourage the output of keywords a penalty is inserted. A novel and inventive aspect of the present invention is the way of determining, presenting and/or handling this penalty so as to make the keyword spotting system more accurate and flexible. A major aspect of the invention is therefore to make
- 10 the penalty or the penalty value variable so as to consider further aspects of the recognition process, of the application situation, of the user preferences or the like. Therefore, the recognition process can be adapted without changing the basic algorithm or processing.
- 15 In a word spotting system the likelihood of a keyword is compared with the likelihood with a garbage word in a garbage model. The added penalty decreases the likelihood of the garbage word in the garbage model and therefore enhances the output of keywords being contained in the keyword model. In most conventional cases the penalty value is added during the transition from the keyword model
- 20 to the garbage model only. If in particular a lattice structure is imagined with different paths with each path representing a possible keyword or a garbage word, every time the system follows a path to a garbage model conventionally a fixed penalty is added and decreases the likelihood of the path from the keyword model to the garbage model.
- 25 In current conventional word spotters the penalty is fixed and added only in the initial transition to the garbage model. Therefore, the system can remain for a long time inside the garbage model within so-called self-transitions, without further penalties being added to the accumulated or global store.
- 30 In contrast, the present inventive method for recognizing speech can further increase the likelihood to move out of the garbage model and to match possible keywords within the keyword model as the penalty is made variable, for instance dependent on the time of the recognition process remaining within the garbage
- 35 model or the recognition step within the garbage model associated therewith.

Additionally, in conventional methods for recognizing speech and in conventional word spotting systems the designer of the method or the system fixes the

MÜLLER &amp; HOFFMANN

- 7 -

Sony International (Europe) GmbH

File: 52.886

13.12.2000

1 penalty. In general the value of the penalty represents a compromise between the number of false accepted keywords, corresponding to a high penalty, and false rejected keywords, corresponding to a low penalty.

5 In contrast, in accordance with the present invention the penalty indeed may depend on the application and/or on the user preferences. For example in a conventional dialogue system with an entertainment robot a false keyword detection can result in strange actions that may also be funny, in particular in a play status. On the other hand, the user could not be in the mood to play and  
10 so wants the robot to do exactly what he asks for, in particular in the action status. According to the invention these circumstances with respect to the application situation and/or to the user preferences can be considered to change and vary the penalty and the penalty values within the garbage model to ensure an adjustment or adaptation of the penalty and the penalty values in accordance  
15 with the aim of the user and/or in accordance with the needs of the application situation.

Additionally conventional word spotting systems have the penalty values defined in a fixed manner within the underlying source code which in general is not accessible by the end user. In accordance with the present invention, the penalty  
20 can now be changed and varied by the user through an user interface to add more flexibility and achieve more new possible applications of the inventive method for recognizing speech. The penalty can therefore be easily accessed and be stored together with model statistical information in an accessible memory,  
25 for example on a hard disk or the like. As a result, existing speech recognition software may be used without changing the source code.

A further aspect of the present invention is that for each step or frame of the recognition process remaining inside the garbage or out-of-vocabulary model a  
30 certain penalty or penalty value can be added to the global score making the global penalty variable. Considering a lattice structure for the keyword and for the garbage model paths with longer stay inside the garbage model are therefore more penalized, while paths with keywords inside are more likely and therefore are output. Therefore, according to the invention the penalty depends on the  
35 time spent by the recognition process or the system inside an out-of-vocabulary or garbage model.

- 1 The method for recognizing speech according to the invention will be explained in more detail taking reference to the accompanying figures.

- 5 **Fig. 1** is a schematical block diagram showing a preferred embodiment of the present invention.

**Fig. 2** is a schematical block diagram showing a conventional method for recognizing speech.

- 10 In the schematical block diagram of Fig. 2 a conventional prior art method 10 for recognizing speech based on penalized keyword spotting is shown in more detail.

- 15 In a first step 11 of said prior art method for recognizing speech a speech phrase SP is received. Said received speech phrase SP is fed into a recognition step or process 12. Based e.g. on a lattice structure of the keyword model KM and the garbage model GM or out-of-vocabulary OOV of an underlying language model LM different paths are checked to find out whether at least one of said possible keywords K1-K3 or one of said garbage words G0-G6 do fit best to  
20 said received speech phrase SP. Likelihoods LKM and LGM' are calculated for the keyword model KM and for the garbage model GM respectively.

- To calculate a penalized likelihood LGM for the garbage model GM a certain pre-defined function f is evaluated on the garbage model likelihood LGM' and on the  
25 fixed global penalty Pglob which is inserted into the language model LM and in particular to the garbage model GM via the transition step T and a respective and fixedly defined transition penalty Ptrans; i.e.  $P_{glob} := P_{trans}$ .

- In a comparison step 13 it is checked whether the keyword model likelihood  
30 LKM is larger than the penalized garbage model likelihood LGM. If so, a recognized speech phrase RSP is accepted and/or output in step 14 as a sequence of recognized keywords or key phrases Kj. Otherwise, the received speech phrase SP is rejected in step 15.

- 35 In contrast to the prior art method shown in Fig. 2 the embodiment of the inventive method according to Fig. 1 employs variable global penalty Pglob. In the embodiment of Fig. 1 said global penalty Pglob indeed is made variable upon the variability of the functional combination of the step and/or time dependent pen-



**MÜLLER & HOFFMANN**

- 9 -

Sony International (Europe) GmbH

File: 52.886

13.12.2000

1 alties P1-P6. Additionally a transition penalty Ptrans for the transition from the keyword model KM to the garbage model GM via the transition step T may also be included and may also be variable.

5 The chosen numbers of seven garbage words G0-G6 on six penalties P1 - P6 above is meant as an illustration only, but not as a limitation of the invention.

10

15

20

25

30

35

**THIS PAGE BLANK (USPTO)**

MÜLLER &amp; HOFFMANN

- 10 -

Sony International (Europe) GmbH

File: 52.886

13.12.2000

1

**Claims****EPO - Munich  
48****13. Dez. 2000****1. Method for recognizing speech,**

- wherein at least keywords (Kj) in a received speech phrase (SP) are recognized employing a keyword spotting based recognition process (12) and a given language model (LM),

5 - wherein a combination of at least one first language or keyword model (KM) containing and/or describing possible in-vocabulary or keywords or phrases (Kj) and one second language or out-of-vocabulary model (OOVM) describing at least in part out-of-vocabulary words or phrases (Gj) is used as said language model (LM), and

10 - wherein a global penalty (Pglob) is associated to and/or introduced or inserted into said language model (LM) so as to increase the recognition of keywords (Kj),  
**characterized in that**

15 at least one variable penalty value (Ptrans, P1, ..., P6) is associated with and/or used to define the global penalty (Pglob).

**2. Method according to claim 1,**

20 wherein said variable penalty value (Ptrans, P1, ..., P6) is in each case made dependent on or a function of the recognition process, of an user input, of a received speech phrase (SP) per se and/or their characteristics or the like.

**3. Method according to anyone of the preceding claims,**

25 wherein at least one statistical model, garbage model (GM) and/or the like is used as said out-of-vocabulary model (OOVM).

**4. Method according to anyone of the preceding claims,**

30 wherein said out-of-vocabulary model (OOVM) and in particular said garbage model (GM) is chosen to contain at least a phone\* grammar or the like.

**5. Method according to anyone of the preceding claims,**

35 wherein said variable penalty value (Ptrans, P1, ..., P6) is associated with a transition (T) of the recognition process (12), in particular from a keyword model (KM) to an out-of-vocabulary model (OOVM).

**6. Method according to anyone of the preceding claims,**

wherein said variable penalty value (Ptrans, P1, ..., P6) is - in particular in each case - associated with a recognition step and/or recognition or process-

MÜLLER &amp; HOFFMANN

- 11 -

Sony International (Europe) GmbH

File: 52.886

13.12.2000

- 1 ing time of said recognition process (12) within said out-of-vocabulary model  
(OOVM) or a garbage model (GM).
7. Method according to anyone of the preceding claims,  
5 wherein a lattice structure of recognition paths or the like is used in said  
keyword model (KM) and/or said out-of-vocabulary (OOVM) or garbage model  
(GM).
8. Method according to claim 7,  
10 wherein with at least a part of said recognition paths in said out-of-vo-  
cabulary (OOVM) is associated a variable penalty value (Ptrans, P1, ..., P6), in  
particular within the statistical information of said out-of-vocabulary model  
(OOVM) or garbage model (GM).
- 15 9. Method according to any of the preceding claims,  
wherein a Markov model, and in particular a single state Markov model, is  
at least contained in said out-of-vocabulary model (OOVM) or garbage model  
(GM), and  
wherein a variable penalty value (P1, ..., P6) is associated with self-transi-  
20 tions of the recognition process within said Markov model.
10. Method according to anyone of the preceding claims,  
wherein a variable penalty value is associated with all transitions in a  
Markov model.
- 25 11. Method according to anyone of the preceding claims,  
wherein said variable penalty value (Ptrans, P1, ..., P6) is made dependent  
on the particular application, the application status and/or on user preferences.
- 30 12. Method according to anyone of the preceding claims,  
wherein said variable penalty value (Ptrans, P1, ..., P6) is varied interac-  
tively, in particular by an user action via an user interface.
13. Method according to anyone of the preceding claims,  
35 wherein said variable penalty value (Ptrans, P1, ..., P6) is hold and stored  
in a randomly accessible manner in particular within the model statistical infor-  
mation of the language model (LM).

MÜLLER &amp; HOFFMANN

- 12 -

Sony International (Europe) GmbH

File: 52.886

13.12.2000

1 14. Method according to anyone of the preceding claims,

wherein likelihoods (LKM, LGM), global scores or the like for recognition results in said keyword model (KM) and in said out-of-vocabulary model (OOVM) - in particular said garbage model (GM) - are determined, the latter of which being variably penalized, and

5 wherein a recognition result (RSP) is accepted with the keyword model likelihood (LKM) being larger than a respective out-of-vocabulary model likelihood (LGM), and is rejected as being out of vocabulary otherwise.

10

15

20

25

30

35

**THIS PAGE BLANK (USPTO)**

MÜLLER &amp; HOFFMANN

- 13 -

Sony International (Europe) GmbH

File: 52.886

13.12.2000

**Abstract**EPO - Munich  
48

13. Dez. 2000

**Method for Recognizing Speech**

To increase the accuracy and the flexibility of a method for recognizing speech which employs a keyword spotting process on the basis of a combination of a keyword model (KM) and a garbage model (GM) it is suggested to associate at least one variable penalty value ( $P_{trans}$ ,  $P_1$ , ...,  $P_6$ ) with a global penalty ( $P_{glob}$ ) so as to increase the recognition of keywords ( $K_j$ ).

(Fig. 1)

**THIS PAGE BLANK (USPTO)**






Fig. 1




Fig. 2